arXiv:1605.06847v1 [cs.IT] 22 May 2016

A simple construction of cover-free (s,ℓ)-code with certain constant weight

A.G. D'yachkov, I.V. Vorobyev, N.A. Polyanskii, V.Yu. Shchukin

Moscow State University, Faculty of Mechanics and Mathematics,
Department of Probability Theory, Moscow, 119992, Russia,
agd-msu@yandex.ru, vorobyev.i.v@yandex.ru, nikitapolyansky@gmail.com, vpike@mail.ru

Abstract. In the given article we generalize a construction presented in [3]. We give a method of constructing a cover-free (s,ℓ)-code. For $k > s$, our construction yields a $\binom{\binom{n}{s}}{\ell} \times \binom{n}{k}$ cover-free (s,ℓ)-code with a constant column weight.

Keywords:. cover-free (s,ℓ)-code; non-adaptive group testing; binary superimposed codes

1 Notations, Definitions and Statement of Problems

Let N, t, s and ℓ be integers, where $1 \le s < t$ and $1 < \ell < t - s$. Let $\triangleq$ denote the equality by definition, $|A|$ – the size of the set A and $[N] \triangleq \{1, 2, \ldots, N\}$ – the set of integers from 1 to N. The standard symbol $\lfloor a \rfloor$ will be used to denote the largest integer $\le a$.

A binary $(N \times t)$-matrix

$$X = \|x_i(j)\|, \quad x_i(j) = 0, 1, \quad i \in [N],\ j \in [t],$$

with N rows $\boldsymbol{x}_1, \ldots, \boldsymbol{x}_N$ and t columns $\boldsymbol{x}(1), \ldots, \boldsymbol{x}(t)$ (*codewords*) is called a *binary code of length N and size $t = \lfloor 2^{RN} \rfloor$*, where a fixed parameter $R > 0$ is called a *rate* of the code X. The number of 1's in a binary column $\boldsymbol{x} = (x_1, \ldots, x_N) \in \{0,1\}^N$, i.e.,

$$|\boldsymbol{x}| \triangleq \sum_{i=1}^{N} x_i, \qquad \boldsymbol{x} \in \{0,1\}^N, \tag{1}$$

is called a *weight* of $\boldsymbol{x}$. A code X is called a *constant weight binary code of weight w*, $1 \le w < N$, if for any $j \in [t]$, the weight $|\boldsymbol{x}(j)| = w$.

Definition 1. [1, 2]. A code X is called a *cover-free (s,ℓ)-code* (briefly, *CF (s,ℓ)-code*) if for any two non-intersecting sets $\mathcal{S}$, Ł $\subset [t]$, $|\mathcal{S}| = s$, |Ł| $= \ell$, $\mathcal{S} \cap$ Ł $= \varnothing$, there exists a row $\boldsymbol{x}_i$, $i \in [N]$, for which

$$\begin{aligned} &x_i(j) = 0 \text{ for any } j \in \mathcal{S}, \\ &x_i(k) = 1 \text{ for any } k \in \text{Ł}. \end{aligned} \tag{2}$$

2 Main Result

Let $\{\binom{n}{k}\}$ denote the family of k-subsets of set $[n]$, and $\{\binom{\binom{n}{s}}{\ell}\}$ denote the family of non-ordered ℓ-tuples of distinct s-subsets of set $[n]$. For $s < k < n$ define a binary matrix $X(k,s,\ell,n)$ by letting the rows and columns be, respectively, represented by the members of $\{\binom{\binom{n}{s}}{\ell}\}$ and $\{\binom{n}{k}\}$ in the following fashion: for given $K \in \{\binom{n}{k}\}$ and given $\mathcal{S} = \{S_1, \ldots, S_\ell\} \in \{\binom{\binom{n}{s}}{\ell}\}$ the matrix

$X(k, s, \ell, n)$ has a 1 in its (K, S)-th entry if and only if there exists at least one $S_i \in \mathcal{S}$ such that $S_i \subset K$.

Theorem 1. *$X(k, s, \ell, n)$ is an $\binom{\binom{n}{s}}{\ell} \times \binom{n}{k}$ cover-free (s, ℓ)-matrix with a constant column weight.*

Proof. Consider arbitrary $\mathcal{S}$ and Ł $\subset [\binom{n}{k}]$, $|S| = s$, $|Ł| = \ell$, $\mathcal{S} \cap Ł = \varnothing$. Let the corresponding elements of $\{\binom{n}{k}\}$ be, respectively, $K_1, \ldots, K_s$ and $K'_1, \ldots, K'_\ell$. Since all elements of $\{\binom{n}{k}\}$ are distinct and of the same size, we can find sets $S_1, \ldots, S_\ell$ such that $S_i \subset K'_i$ and $S_i \not\subset K_j$ for any $i \in [\ell]$ and $j \in [s]$. Therefore, the row which corresponds to the set $\{S_1, \ldots S_\ell\}$ satisfies cover-free (s, ℓ)-condition (2). Observe that the matrix $X(k, s, \ell, n)$ is a constant-weight matrix because all columns of the matrix possess the same properties. □

One can check that we have to choose $k = n/2$ to maximize the size of code X. In asymptotic regime the parameters of $X(n/2, s, \ell, n)$ are:

$$t = 2^{n(1+o(1)}, \quad N = \frac{n^{s\ell}}{(s!)^\ell \ell!}(1 + o(1)).$$

References

[1] *Mitchell C.J.*, *Piper F.C.*, "Key storage in Secure Networks", *Discrete Applied Mathematics*, v. 21, pp. 215-228, 1988.

[2] *A. G. Dyachkov*, *P. Vilenkin*, *A. Macula*, and *D. Torney*, "Families of finite sets in which no intersection of sets is covered by the union of s others", *J. Combin. Theory.* Ser. A, 99 (2002), pp. 195-218.

[3] A. J. Macula, A simple construction of d-disjunct matrices with certain constant weights. Discrete Math., Ser. A, **162**:1-3 (1996), 311312.